



EC-A1688JD4

16T Industrial-Grade Intelligent Computing AI Computer

V1.0 2025-5-13

T-CHIP INTELLIGENCE TECHNOLOGY






Product features



32T INT4/16T INT8 Computing power

Equipped with SOPHON computing AI processor BM1688, it has an octa-core ARM Cortex-A53, with a maximum frequency of 1.6GHz, and a built-in neural network acceleration engine TPU, with 32T@INT4 peak computing power, 16T@INT8 peak computing power, 4T@FP16/BF16 computing power, and 0.5T@FP32 computing power.



Powerful multi-channel video AI processing performance

It supports up to 16 channels of H.265/H.264 1080P video decoding, 10 channels of H.265/H.264 1080P video encoding, and 16 channels of 1080P HD video full-process processing (decoding + AI analysis), meeting the needs of various AI application scenarios such as video streaming face detection, license plate recognition, and smart cities.



The private deployment of large language models

Support the private deployment of ultra-large-scale parameter models under the Transformer architecture, including large language models such as Gemma-2B, LLaMa2-7B, and Qwen1.5-1.8B, ChatGLM3-6B. Support Docker container management technology.



Multiple deep learning frameworks


Support traditional network architectures such as CNN, RNN, and LSTM; a variety of deep learning frameworks, including TensorFlow, Pytorch, PaddlePaddle, Caffe and ONNX, as well as custom operator development.

Product features



All-aluminum alloy enclosure for passive heat dissipation

The industrial-grade all-metal enclosure with aluminum alloy structure for thermal conduction. The side of the top cover features a grille design for external airflow and efficient passive heat dissipation.



Abundant expansion interfaces

It has HDMI2.0, PCIe2.0, USB3.0, RS485, RS232, CAN, TF Card, SIM Card, Type-C and other expansion interfaces. These interfaces facilitate the connection of various peripherals, supporting product applications across various fields.



A wide range of applications


Efficiently compatible with all AI algorithms on the market, it is widely applied to AI servers, edge computing boxes, industrial PCs, smart IP cameras, and AIoT devices, improving various industries through AI.

Specifications




Specification		
Basic Specifications	SOC	SOPHON BM1688
	CPU	Octa-core 64-bit ARM Cortex-A53 @ 1.6GHz
	TPU	Built-in SOPHGO neural network acceleration engine TPU, 32T@INT4 peak computing power, 16T@INT8 peak computing power, 4T@FP16/BF16 computing power, 0.5T@FP32 computing power
	ISP	Time-sharing multiplexing for up to 6 sensor input videos, with maximum widths of 4608 (non-tile mode) and 8192 (tile mode) Supports Sensor self-band dynamic and 2-frame wide dynamic range, and the maximum performance supports: 12M@30 HDR or 8K@15 SDR or 16M@30 SDR Support RGB-IR, AI ISP interface, 3A (AE/AWB/AF, 3A control user adjustable) Support fixed mode noise removal, dead pixel correction, shadow correction, lens distortion correction, purple edge correction, Bayer noise reduction, 3D denoising, image edge enhancement, dehazing, dynamic contrast enhancement, image video Mirror, Flip and other functions
	Decoding/Encoding	Video decoding: H.265/H.264 decoding (maximum performance: 1920×1080@480fps or 8192×4320@30fps) Video encoding: H.265/H.264 encoding (maximum performance: 1920×1080@300fps or 8192×4320@15fps) Image codec: Support JPEG/MJPEG Baseline codec (JPEG codec: 1080P@480fps, maximum resolution 32768×32768)
	RAM	8GB LPDDR4 (4GB/8GB/16GB optional)
	Storage	32GB eMMC (32GB/64GB/128GB/256GB optional)
	Storage Expansion	1 × TF Card, M.2 SATA3.0/PCIe NVMe SSD 2242/2260/2280 (inside the device), scalable SATA3.0 SSD (inside the device)
	OS	Linux OS
	Software Support	<ul style="list-style-type: none"> The private deployment of ultra-large-scale parameter models under the Transformer architecture, including large language models such as Gemma-2B, LLaMa2-7B, ChatGLM3-6B, Qwen1.5-1.8B. Traditional network architectures such as CNN, RNN, and LSTM; a variety of deep learning frameworks, including TensorFlow, Pytorch, PaddlePaddle, Caffe and ONNX, as well as custom operator development Docker container management technology
	Power	DC 12V (5.5mm × 2.1mm, support 9V~24V wide voltage input)
	Power consumption	Normal: 7.2W(12V/600mA), Max: 12W(12V/1000mA)
	Size	188.0mm × 88.44mm × 50.65mm
	Weight	Net weight: 0.79kg, Total weight with packaging: 1.14kg
	Environment	Operating Temperature: -20°C ~ 60°C, Storage Temperature: -20°C ~ 70°C, Storage Humidity: 10% ~ 90%RH (non-condensing)
Interface Specifications	Internet	Ethernet: 2 × RJ45 (1000Mbps) WiFi: Extend WiFi/Bluetooth module via M.2 E-KEY (2230), supports 2.4GHz/5GHz dual band WiFi6 (802.11a/b/g/n/ac/ax) and Bluetooth 5.2 4G: Extend 4G LTE via Mini PCIe (Reused with 5G) 5G: Extend 5G via M.2 B-KEY (Reused with 4G and USB3.0(1), not pasted by default)
	Video output	1 × HDMI2.0 (4K@60fps)
	Audio output	1 × 3.5mm Audio jack (support MIC recording, American standard CTIA)
	USB	2 × USB3.0 (Max: 1A; UP: USB3.0(1), reused with 5G; DOWN: USB3.0(2))
	Other interface	1 × Type-C (DEBUG), 1 × SIM Card 1 × Phoenix connector (2×4PIN, 3.5mm pitch): 1 × RS485, 1 × RS232, 1 × CAN 2.0


Interface description



232-TX	GND	CAN_H	485_A
232-RX	GND	CAN_L	485_B



Dimension





T-CHIP INTELLIGENCE TECHNOLOGY



Contact Us
(+86)18688117175



E-mail
global@t-firefly.com



Website
<https://en.t-firefly.com/>



Address
Room 2101, Hongyu Building, #57 Zhongshan 4Rd, East District,
Zhongshan, Guangdong, China.